



**Oktopus
Stretto**

INTEGRAL CONTROL SPRAYER

Double flip-over nozzles
with drop-stop on
adjustable modules



Adjustable spouts
for airstream
outlet



SPECIFICATIONS

- TRACTOR MOUNTED AND TRAILED INTEGRAL CONTROL SPRAYER
- HIGH PRECISION SPRAYING WITHOUT WASTE
- ESPECIALLY SUITED FOR NARROW AND LOW VINEYARDS AND ORCHARDS
- POLYETHYLENE TANK WITH 3 FULLY INDEPENDENT TANKS
- GALVANIZED FRAME AND CENTRIFUGAL UNIT
- OUTSIDE SUCTION FILTER WITH ANTI-EMPTYING VALVE
- INTERCHANGEABLE DOUBLE FLIP-OVER NOZZLES WITH DROP-STOP ON INDEPENDENT DIRECTIONAL SUPPORTS FROM AIR FLOW
- POSSIBILITY OF AIR OUTPUT SPOUTS WIDTH AND HEIGHT POSITIONING AND ORIENTATION
- 2-SPEED GEARBOX AND NEUTRAL
- TURBINE (CENTRIFUGAL FAN)
- BRASS SINGLE-LEVER REMOTE CONTROL UNIT WITH PRESSURE REGULATOR AND 2 MANUAL WAYS WITH CONSTANT PRESSURE



Self cleaning
high pressure filter

HIGHLIGHTS

Tractor mounted from 300 to 600 L tank and trailed from 600 to 1000 L tank.

From 52 to 110 L/1' pump.

Wide choice of equipment and versions.

Possibility to fit booms on.

Self cleaning filters and hydraulic circuit with maintenance.

High-compact dimensions.

ADVANTAGES FOR THE USER

Broad range of options.


Versatile and suitable for any kind of use.

Possibility of several works with one machine.

Possibility of working with ever clean machine and in best conditions.

Suited for narrow and low plants.

Model	Tank	Pump	Turbine					Power		Dimensions			Weight
			Ø	rpm	m/sec	mc/h	HP	kW	A mm	B mm	C mm		
43-300 06SP	300	rpm = 540 bar 0-50 L/1'	430	2700	60	11600	1-4	30-35	18-26	1750	1000	1455	281
43-400 06SP	400									1750	1210	1650	295
43-500 06SP	500	52	430	2700	60	11600	1-4	30-35	18-26	1750	1210	1650	300
43-600 06SP	600	1750								1210	1650	305	
43-400 08SP	400	81	430	2700	60	11600	1-4	30-35	18-26	1750	1210	1850	325
43-500 08SP	500									1750	1210	1850	330
43-600 08SP	600	52	430	2700	60	11600	1-4	30-35	18-26	1750	1210	1850	335
43-600 06ST	600	3100								1000	2000	400	
43-800 06ST	800	110	430	2700	60	11600	1.5-4	35-40	26-30	3100	1200	2150	440
43-600 08ST	600									3100	1000	2200	430
43-800 08ST	800	110	430	2700	60	11600	1.5-4	35-40	26-30	3100	1200	2350	470
43-1001 08ST	1000									3100	1350	2350	570





INTEGRAL CONTROL SPRAYER



TRACTOR MOUNTED SPRAYER OKTOPUS STRETTO

CODE	TRACTOR MOUNTED SPRAYER OKTOPUS STRETTO
700625	OKTOPUS 43-300 06SP L/52
703636	OKTOPUS 43-400 06SP L/52
703637	OKTOPUS 43-500 06SP L/52
703638	OKTOPUS 43-600 06SP L/52
703639	OKTOPUS 43-400 08SP L/81
703640	OKTOPUS 43-500 08SP L/81
703641	OKTOPUS 43-600 08SP L/81
004780	PTO shaft HP47 L 910 "CE"

TRAILED SPRAYER OKTOPUS STRETTO

CODE	TRAILED SPRAYER OKTOPUS STRETTO
700453	OKTOPUS 43-600 06ST L/52
700761	OKTOPUS 43-800 06ST S/95
700671	OKTOPUS 43-600 08ST S/95
700762	OKTOPUS 43-800 08ST S/95
701968	OKTOPUS 43-1001 08ST S/95
004741	PTO shaft HP47 L 710 "CE"

EQUIPMENT

CODE	DESCRIPTION
400879	Charge turbine ø430->ø450

EQUIPMENT SEE TABLE AT PAGE 19 - TRACTOR MOUNTED

EQUIPMENT SEE TABLE AT PAGE 29 - TRAILED

FOR CHARGE ELECTRIC CONTROL KIT SEE PAGE 54