


NOBILI



OKTOPLUS FF PRO

Irroratrice scavallante

Over-the-row sprayer



OKTOPUS FF PRO

Irroratrice scavallante

La nuova testata **OKTOPUS FF PRO** risponde alle esigenze delle nuove realtà operative del vigneto, consentendo tempi di intervento ridotti, tempestività e precisione nei trattamenti.

Grazie all'innovativa girante 503 (optional) e al suo convogliatore viene garantita la medesima distribuzione dell'aria su tutte le bocchette che sono montate su calate ad alimentazione indipendente e che permettono un'uniformità di trattamento su tutta la parete fogliare di ciascuna facciata. I movimenti della testata permettono di aprire e chiudere le calate anche all'interno dei filari, scavallando con agilità altezze di 2,4 m rimanendo all'interno dei filari stessi ed evitando ostacoli pericolosi o che possono rallentare il lavoro (pali della luce a centro filare). Le tre calate verticali sono montate su bracci telescopici che permettono di trattare impianti di vigneto con larghezze interfilari fino a 3,5 m e pareti vegetate fino a 2,5 m, trattando tre file complete. Nelle bocchette sono montati getti antideriva che consentono di poter modulare la potenza della aria senza compromettere la qualità di micronizzazione.

Over-the-row sprayer


The new spray head **OKTOPUS FF PRO** meets the needs of the new operational realities in vineyard and enables reduced intervention times, timeliness and precision in treatments.

Thanks to the innovative centrifugal fan 503 (optional) and its conveyor unit, the same air distribution is guaranteed through all spouts, which are mounted on independently fed arms allowing uniformity of treatment over the entire leaf canopy of each face.

The movements of the spray head make possible to open and close the arms even inside the rows, easily crossing over heights of 2,4 m - remaining inside the rows themselves - avoiding dangerous obstacles or obstacles that can slow down the work (lampposts in the middle of the rows). The three vertical arms are mounted on telescopic arms that enable to treat vineyard plants with inter-row widths of up to 3,5 m and leaf canopy up to 2,5 m, treating three complete rows. Anti-drift jets are mounted in the nozzles which allow the air power to be modulated without compromising the micronization quality.



Caratteristiche tecniche - Technical Specifications

OKTOPUS FF PRO												
	L	rpm=540 bar 0-20 L/1'	Ø	rpm	m/sec	mc/h	HP	kW	A mm	B mm	C mm	Kg-Lbs
OKTOPUS 1002 T	1000	120	500 D.A.	4180	185	13.800	80-90	59-66	3800	2150	2410	1200 - 2646
OKTOPUS 1502 T	1500	160					80-90	59-66	4000	2150	2620	1300 - 2866
OKTOPUS 2002 T	2000	160					80-90	59-66	4280	2150	2700	1400 - 3086
OKTOPUS 3002 T	3000	170					90-100	66-81	4825	2550	2950	1690 - 3726

Concessionario / Dealer

NOBILI

40062 MOLINELLA (Bologna) - Italy - Tel. +39 051 881444
www.nobili.com - info@nobili.com

